

Application	1st Choice				2nd Choice			
	Monovalve Float Bimetallic® Multi-Segment Bimetallic®	Piston Operated®	Thermodynamic	Monovalve Float Bimetallic® Multi-Segment Bimetallic®	Piston Operated®	Thermodynamic		
Steam Mains								
0-15 psig	✓					✓		
15-600 psig								✓
to 1500 psig								✓
to 2500 psig								✓
to 4500 psig								✓
with Superheat								✓
Separators	✓						✓	
Steam Tracer								
Critical								✓
Non-Critical								✓
Heating Equipment								
Shell & Tube Heat Exchangers	✓						✓	
Heating Coils	✓						✓	
Unit Heaters	✓					✓		
Plate & Frame Heat Exchangers	✓						✓	
Radiators		✓						
General Process Equipment								
to 200 psig	✓							
to 600 psig		✓						
to 900 psig		✓						
to 1500 psig		✓						
Hospital Equipment								
Autoclaves	✓					✓		
Sterilizers	✓					✓		
Fuel Oil Heating								
Bulk Storage Tanks		✓			✓			
Line Heaters	✓							
Tanks & Vats								
Bulk Storage Tanks		✓			✓			
Process Vats	✓							✓
Vulcanizers	✓							✓
Evaporators	✓							✓
Reboilers			✓			✓		
Rotating Cylinders	✓							
Freeze Protection		✓						